



Fax: +86 (512) 5011 2656

INSPEC Technical Services (Kunshan) Co Ltd • 8 Jin Yang East Road • Lu Jia Zhen • Kunshan • Jiangsu • China Email: testing@inspec.asia Website: www.inspec-international.com

Tel: +86 (512) 5011 2646

# **Test Report**

# PPE against fall from a height EN 361: 2002 Full body harnesses

Report no: 2.19.06.05

Client: Portwest Ltd.

Portwest House

Westport Business and Technology Park

Westport County Mayo

Eire

Manufacturer: Portwest Ltd.

Client order: T/0613

Order received: 10 June 2019

Model: FP14

Dates of tests: 14 June 2019 to 18 June 2019

Signed: Issued: 21 June 2019

Steven Sum, Laboratory Manager Page 1 of 7

#### Conditions

This report may be reproduced and distributed to your clients, provided that it is reproduced and distributed in full.

Specimens will be disposed of four weeks from the date of this report, unless otherwise instructed.

Opinions, comments and interpretations expressed in this report are shown in italics.

Copies of INSPEC interpretations referenced in this report are available upon request.

Tests marked are not included in our ANAB Scope of Accreditation.

DEC!

This report has been provided in accordance with our standard Terms of Business, which can be viewed at, and printed from:

ECH

BECH

BECH

http://inspec-international.com/ToB.pdf

ESH

ECH

If you have difficulty accessing the Terms of Business, you may contact us for a copy

#### INSPEC Test Report No: 2.19.06.05

BECH

BECH

#### Summary of assessment\*

| Clause | Requirement                | Assessment<br>(See Key) |
|--------|----------------------------|-------------------------|
| 4.1    | Design & ergonomics        | 16001                   |
| 4.2    | Materials and construction |                         |
| 4.3    | Static strength            |                         |
| 4.4    | Dynamic performance        | Pass                    |
| 4.5    | Additional elements        |                         |
| 4.6    | Marking and information    |                         |
| 6      | Marking                    |                         |
| 7      | Information                | Para -                  |
| 8      | Packaging                  | 19/1-                   |

ELECH

#### Key

|      | Shading shows the clauses requested. Any other clauses were not requested.   |  |  |
|------|--|--|--|
| Pass | Requirement satisfied.   |  |  |
| Ltd  | Testing requested was insufficient completely to verify compliance with the clause Refer to the "Result details" section for more information. |  |  |
| Fail | Requirement not satisfied. Refer to the "Result details" section for more information.   |  |  |
| NAs  | Assessment not carried out.  |  |  |
| NAp  | Requirement not applicable.  |  |  |
| NT   | Requested but not tested due to early termination following failure.   |  |  |

Assessment relates only to those specimens which were tested and are the subject of this report.



PECH

INSPEC Test Report No: 2.19.06.05

#### Submission details

| Product                       | Quantity | Date received | INSPEC specimen no.<br>(2G083+) |  |
|-------------------------------|----------|---------------|---------------------------------|--|
| Full body harness, model FP14 | 03       | 4 June 2019   | 01 to 03                        |  |

#### Procedures

The specimens detailed within the submissions above were used for the tests covered by this report.

Testing was performed in accordance with EN 361:2002 unless otherwise specified below. Reference should be made to the standard when reading this report.

Unless stated otherwise, specimens were tested in the condition as received by INSPEC.

Testing was performed at INSPEC's laboratory in Kunshan, China.

The client requested testing to clause 4.4 Dynamic Performance only. No other clauses were assessed



ECH

#### Result details

#### 4.4 Dynamic performance

Specimen 2G08301 was tested

When the specimen was tested at the back attachment element, the harness withstood the feet-first drop test without releasing the torso dummy and without rupturing. The torso dummy was arrested in the head-up position and the angle of its back to the vertical was 11 degrees, which is less than the maximum 50 degrees permitted. Pass

When the specimen was tested at the back attachment element, the harness withstood the head-first drop test without releasing the torso dummy and without rupturing. The torso dummy was arrested in the head-up position and the angle of its back to the vertical was 12 degrees, which is less than the maximum 50 degrees permitted.

ECH

ESH

ECH

DECH

Pass

ECH

ECH

ECH

MECH

#### Estimates of the uncertainty of measurement

| Clause | Test                       | Uncertainty |
|--------|----------------------------|-------------|
| 4.1    | Design & ergonomics        | -           |
| 4.2    | Materials and construction | COL         |
| 4.3    | Static strength            | ±3.5%       |
| 4.4    | Dynamic performance        | ±0.8%       |
| 4.5    | Additional elements        | See report  |
| 4.6    | Marking and information    |             |
| 6      | Marking                    | -           |
| 7      | Information                | -           |
| 8      | Packaging                  |             |

<sup>\*</sup> The acceptance criterion for this test is a straightforward "Pass/Fail", rather than a numerical value. Consequently, as there is no value to be reported, uncertainty has not been reported either.

Values expressed as a percentage (%) are relative.

BECH

ECH:

It should be noted that the above values have not been taken into account when making assessment to the pass/fail criteria.



ECH

ECH

BIECH.

## ANNEX

E LECH

This Annex comprises one section.

Photograph of the product tested.

ECH

ECH

BECH

ECH

(1 page)

BECH

BECH

BECH

END OF REPORT

### Portwest Ltd. – Full body harness, model FP14





DECI

ES!