

Test Report

Personal fall protection equipment EN 354: 2010 Lanyards

Report no: 2.19.07.08

Client: Jinhua Jech Tools Co., Ltd
No.10 Jinlong Road
Baillongqiao Town
Jinhua City, Zhejiang
China

Manufacturer: Jinhua Jech Tools Co., Ltd

Client order: T/0596A

Order received: 16 May 2019

Model: JE900018

Dates of tests: 19 June 2019 to 13 August 2019

Signed:



Steven Sum, Laboratory Manager

Issued: 15 August 2019

Page 1 of 14

Conditions

This report may be reproduced and distributed to your clients, provided that it is reproduced and distributed in full.

Specimens will be disposed of four weeks from the date of this report, unless otherwise instructed.

Opinions, comments and interpretations expressed in this report are shown in italics.

Copies of INSPEC interpretations referenced in this report are available upon request.

Tests marked are not included in our ANAB Scope of Accreditation.

This report has been provided in accordance with our standard Terms of Business, which can be viewed at, and printed from:

<http://inspec-international.com/ToB.pdf>

If you have difficulty accessing the Terms of Business, you may contact us for a copy.

Summary of assessment*

Clause	Requirement	Assessment (See Key)
4.1	Design & ergonomics ①	Pass
4.2	Materials	Ltd
4.3	Terminations	Pass
4.4	Slippage - adjustable length lanyards ①	
4.5	Static strength ①	Pass
4.6	Dynamic strength - adjustable length lanyards	
4.6	Static strength after dynamic strength - adjustable length lanyards	
4.7	Corrosion resistance	
4.8	Marking and information	See 6 and 7 below
6	Marking	Pass
7	Information supplied by the manufacturer	Pass
8	Packaging	NAs

① INSPEC Interpretation applies

Key

	Shading shows the clauses requested. Any other clauses were not requested.
Pass	Requirement satisfied.
Ltd	Testing requested was insufficient completely to verify compliance with the clause. Refer to the "Result details" section for more information.
Fail	Requirement not satisfied. Refer to the "Result details" section for more information.
NAs	Assessment not carried out.
NAp	Requirement not applicable.
NT	Requested but not tested due to early termination following failure.

* Assessment relates only to those specimens which were tested and are the subject of this report.

Submission details

Product	Quantity	Dates received	INSPEC specimen no. (2G079+)
Lanyard, model JE900018	02	5 June 2019	01 to 02

Procedures

The specimens detailed within the submissions above were used for the tests covered by this report.

Testing was performed in accordance with EN 354:2010 unless otherwise specified below. Reference should be made to the standard when reading this report.

Unless stated otherwise, specimens were tested in the condition as received by INSPEC.

Testing was performed at INSPEC's laboratory in Kunshan, China.

- 4.8 As per client's instructions, labels and information supplied electronically were used for assessment

Result details**4.1 Design and ergonomics**

Specimen 2G07902 was assessed.

- | | | |
|-------|--|------|
| 4.1.1 | The materials of construction were smoothly finished and did not have sharp edges or burrs that may cause injury or may cut, abrade or otherwise cause damage to the lanyard itself. | Pass |
| 4.1.2 | The specimen did not incorporate a length adjustment device. Therefore, this clause is not applicable. | NAp |
| 4.1.3 | This clause is not applicable to the type of lanyard tested. | NAp |
| 4.1.4 | This clause is not applicable to the type of lanyard tested. | NAp |
| 4.1.5 | There were no connectors incorporated into the lanyard. | NAp |
| 4.1.6 | The length of the specimen was marked "1.0 m".
The length of the specimen, measured to the nearest 5 mm between load bearing points, was 985 mm. This is within $\pm 5\%$ of the marked length. | Pass |

4.2 Materials

Specimen 2G07902 was assessed.

- | | | |
|-------|---|-----|
| 4.2.1 | Possible effects of contact by materials of the lanyard with the skin of the user were not assessed. Manufacturer to certify. | NAs |
| 4.2.2 | The materials used for fibre rope, webbing and threads and their characteristics were not assessed. Manufacturer to certify. | NAs |
| 4.2.3 | The specimen was not a wire rope. Therefore this clause is not applicable. | NAp |
| 4.2.4 | The specimen was not a chain. Therefore this clause is not applicable. | NAp |

4.3 Terminations

Specimen 2G07902 was assessed.

- | | | |
|-------|--|------|
| 4.3.1 | Both ends of the lanyard were terminated with a stitched eye loop termination. Hence the lanyard can be connected to other personal fall protection equipment by an appropriate connector. | Pass |
| 4.3.2 | The lanyard did not incorporate spliced terminations, therefore this clause was not applicable. | NAP |
| 4.3.3 | Threads used for sewing the lanyard were black colour. This contrasted with the yellow colour of the lanyard material. | Pass |
| 4.3.4 | Knots were not used in the terminations, therefore this clause was not applicable. | NAP |
| 4.3.5 | The ends of the lanyard were hot-cut to prevent them from unravelling. | Pass |
| 4.3.6 | This clause is not applicable to the type of lanyard tested. | NAP |

4.5 Static strength – single lanyard (fixed length)

- | | | |
|-------|--|------|
| 4.5.1 | Specimen 2G07902 was assessed.

When tested in accordance with 5.7, the specimen withstood the 22 kN force applied for 3 minutes without separating, tearing or rupturing. | Pass |
| 4.5.2 | This clause is not applicable to the type of lanyard tested. | NAP |

4.8 Marking and information - see clauses 6 and 7 below.

6 Marking

Labels were supplied electronically and used for assessment against the specific requirements of EN 354 and the results are detailed below.

Results were also assessed against the requirements specified in clause 4.8 of EN 365:2004 and are given on page 8 of this report.

- | | | |
|----|--|------|
| a) | The lanyard was marked with its maximum length, thus "1.0 m". | Pass |
| b) | The lanyard was marked with the month and year of manufacture, thus "06/2019". | Pass |

7 Information supplied by the manufacturer

Electronic copy of information was assessed against the specific requirements of EN 354 and the results are detailed below.

Results of the assessment of the same information against the requirements specified in clause 4.1 to 4.7 of EN 365:2004 are given from page 9 to 12 of this report.

The information supplied by the manufacturer shall conform to EN 365 and, in addition, shall include at least advice or information as follows:

- | | |
|---|---------|
| a) that the user should read and understand the information supplied by the manufacturer before using the lanyard; | a) Pass |
| b) that a lanyard shall not be used for fall arrest purposes without any energy absorption, e.g. an energy absorber; | b) Pass |
| c) that the total length of a lanyard connected to an energy absorber (including terminations and connectors) shall not exceed 2 m; | c) Pass |
| d) the material from which the lanyard is made; | d) Pass |
| e) the number of this European Standard, i.e. EN 354:2010; | e) Pass |
| f) that, if the risk assessment carried out before the start of work shows that loading in the case of a use over an edge is possible, appropriate precautions should be taken; | f) Pass |
| g) that the user should minimise the amount of slack in the lanyard near a fall hazard; | g) Pass |
| h) when adjusting the length of a lanyard to avoid the risk of fall, the user should not move into an area where there is a fall hazard; | h) NAP |
| i) the useable life of the product and recommendations/information where the life expectancy could be reduced; | i) Pass |
| j) information on whether the lanyard may be used choke hitched; | j) Pass |
| k) information on the allowed/disallowed arrangements/configuration of lanyards when combined with an energy absorber. | k) Pass |

Non-exhaustive examples are:

- 1) Two separate lanyards each with an energy absorber should not be used side by side (i.e. parallel);
- 2) The free tail of a twin tail lanyard combined with energy absorber should not be clipped back on the harness.

8 Packaging

Not assessed. Manufacturer to certify.

NAs

EN 365:2004, Clause 4.8, Marking

4.8.1 Each item of PPE or other equipment shall be clearly, indelibly and permanently marked by the manufacturer in the official language of the country of destination, by any suitable method not having a harmful effect on the materials so marked, and shall include at least:

The language assessed was English.

a) means of identification, e.g. manufacturer's name, supplier's name, or trademark; **Pass**

Note 1. When PPE is marked with the supplier's name this should be with the approval of the Notified Body.

b) manufacturer's production batch or serial number or other means of traceability; **Pass**

c) model and type/identification; **Pass**

d) number and year of the document to which the equipment conforms; **Pass**

e) pictogram or other method to indicate the necessity for users to read the instructions for use; **Pass**

Note 2: Any additional relevant marking specific to the item of equipment should also be included

4.8.2 The characters in the markings shall be legible and unambiguous. **Pass**

EN 365:2004, Clause 4.1 to 4.7, Instructions**4.1 General**

The manufacturer shall prepare instructions for use, for maintenance and for periodic examination for each item of PPE or other equipment, in the official languages of the country of destination.

The language assessed was English.

Note. The instruction for use, for maintenance and for periodic examination may be supplied in separate documents.

4.2 Instructions for use

4.2.1 The instructions for use shall be in a written format, shall be clear, legible and unambiguous, and shall contain appropriate detail, supplemented by diagrams if necessary, to enable the PPE or other equipment to be used correctly and safely. Pass

4.2.2 The instructions for use shall include:

- | | |
|---|------|
| a) name and contact details of the manufacturer or authorised representative as appropriate; | Pass |
| b) statements describing the equipment, its intended purpose, application and limitations; | Pass |
| c) warning about medical conditions that could affect the safety of the equipment user in normal and emergency use; | Pass |
| d) warning that the equipment shall only be used by a person trained and competent in its safe use; | Pass |
| e) warning that a rescue plan shall be in place to deal with any emergencies that could arise during the work; | Pass |
| f) warning against making any alterations or additions to the equipment without the manufacturer's prior written consent, and that any repair shall only be carried out in accordance with manufacturer's procedures; | Pass |
| g) warning that the equipment shall not be used outside its limitations, or for any purpose other than that for which it is intended; | Pass |
| h) advice as to whether the equipment should be a personal issue item, where this is applicable; | Pass |
| i) sufficient information to ensure the compatibility of items of equipment when assembled into a system; | Pass |
| j) warning of any dangers that may arise by the use of combinations of items of equipment in which the safe function of any one item is affected by or interferes with the safe function of another; | Pass |
| k) instruction for the user to carry out a pre-use check of the equipment, to ensure that it is in a serviceable condition and operates correctly before it is used; | Pass |

Note1. A pre-use check by the user may not be applicable in the case of certain parts of equipment for emergency use which have been pre-packed or sealed by a competent person.

- | | |
|--|------|
| l) features of the equipment that require the pre-use check, the method of checking, and the criteria against which the user can decide whether or not the equipment is defective; | Pass |
|--|------|

- | | | |
|----|---|------|
| m) | warning stating that it is essential for safety that equipment is withdrawn from use immediately should: | |
| | 1) any doubt arise about its conditions for safe use or; | Pass |
| | 2) it have been used to arrest to fall | Pass |
| | and not used again until confirmed in writing by a competent person that it is acceptable to do so; | |
| n) | requirements of the anchor device or structural member chosen to serve as the anchor point(s), in particular the minimum required strength, the suitability and the position; | Pass |
| o) | where relevant, instruction on how to connect to the anchor device or structure; | Pass |
| p) | where relevant, an instruction detailing the correct harness attachment point to use, and how to connect to it; | Pass |
| q) | for equipment intended for use in fall arrest systems, a warning to emphasise that it is essential for safety that the anchor device or anchor point should always be positioned, and the work carried out in such a way, as to minimise both the potential for falls and potential fall distance. Where it is essential that the anchor device/point is placed above the position of the user, the manufacturer shall make a statement to that effect; | Pass |
| r) | where relevant, an instruction that a full body harness is the only acceptable body holding device that can be used in a fall arrest system; | Pass |
| s) | for equipment intended for use in fall arrest systems, a warning to emphasise that it is essential for safety to verify the free space required beneath the user at the workplace before each occasion of use, so that, in the case of a fall, there will be no collision with the ground or other obstacle in the fall path; | Pass |
| t) | information on the hazards that may affect the performance of the equipment and corresponding safety precautions that have to be observed, e.g. extremes of temperature, trailing or looping of lanyards or lifelines over sharp edges, chemical reagents, electrical conductivity, cutting, abrasion, climatic exposure, pendulum falls; | Pass |
| u) | instruction as relevant on how to protect the equipment against damage during transportation; | Pass |
| v) | information on the meaning of any markings and/or symbols on the equipment; | Pass |
| w) | statement describing the equipment model, type, identification marks and, if appropriate, the document and year to which it conforms; | Pass |
| x) | where it is a requirement that an EC type examination be carried out by a Notified Body, the name, address and identification number of the Notified Body involved with the design stage and of the Notified Body involved in the production control phase; | Pass |
| y) | statement of any known limit to the safe useable life of the product or any part of the product and/or advice on how to determine when the product is no longer safe to use; | Pass |
| z) | warning that it is essential for the safety of the user that, if the product is re-sold outside the original country of destination, the reseller shall provide instructions for use, for maintenance, for periodic examination and for repair in the language of the country in which the product is to be used. | Pass |

Note 2. Any additional relevant information specific to the item of equipment should also be provided.

4.3 Instructions for maintenance

4.3.1 The maintenance instruction shall be clear, legible and unambiguous, and shall contain appropriate detail, supplemented by diagrams if necessary, to enable the PPE or other equipment to be maintained correctly and safely. Pass

4.3.2 The maintenance instructions shall include:

- a) cleaning procedures, including disinfection where applicable, without causing adverse effect on the materials used in the manufacture of the equipment, or to the user, and a warning that the procedure is to be strictly adhered to; Pass
- b) where appropriate, a warning that, when the equipment becomes wet, either from being in use or when due to cleaning, it shall be allowed to dry naturally, and shall be kept away from direct heat; Pass
- c) storage procedures, including all necessary preventative requirements where environmental or other factors could affect the condition of components, e.g. damp environment, sharp edges, vibration, ultraviolet degradation; Pass
- d) other maintenance procedures as relevant to the equipment, e.g. lubrication. NAp

4.4 Instructions for periodic examination

Instructions for periodic examination shall include:

- a) warning to emphasize the need for regular periodic examinations, and that the safety of users depends upon the continued efficiency and durability of the equipment; Pass
- b) recommendation in regard to the frequency of periodic examinations, taking account of such factors as legislation, equipment type, frequency of use, and environmental conditions. The recommendation shall include a statement to the effect that the periodic examination frequency shall be at least every 12 months; Pass
- c) warning to emphasize that periodic examinations are only to be conducted by a competent person for periodic examination and strictly in accordance with the manufacturer's periodic examination procedures; Pass
- d) where deemed necessary by the manufacturer, e.g. due to the complexity or innovation of the equipment, or where safety critical knowledge is needed in the dismantling, reassembly, or assessment of the equipment, (e.g. a retractable type fall arrester), an instruction specifying that periodic examinations shall only be conducted by the manufacturer or by a person or organisation authorised by the manufacturer; Pass
- e) requirement to check the legibility of the product markings. Pass

4.5 Instructions for repair

Where the manufacturer permits repair, repair instructions shall be supplied in the official languages of the country in which the item is in service. These instructions shall include a statement to the effect that any repair shall only be conducted by a competent person for repair, who has been authorised by the manufacturer, and that the repair procedure shall be strictly in accordance with the manufacturer's instructions. NAp

Repair was not permitted by the manufacture.

4.6 Records

Advice shall be given that a record is kept for each component, subsystem and system. The record should contain headings for, and spaces to allow entry of, the following details:

- | | |
|--|------|
| a) product, (e.g. full body harness), model and type/identification and its trade name; | Pass |
| b) name and contact details of the manufacturer or supplier; | Pass |
| c) means of identification, which could be the batch or serial number; | Pass |
| d) where applicable, the year of manufacturer or life expiry date, (refer to 4.2.2 y); | Pass |
| e) date of purchase; | Pass |
| f) any other information as necessary, e.g. maintenance and frequency of use; | Pass |
| g) date first put into use; | Pass |
| h) history of periodic examinations and repairs, to include: | |
| 1) dates and details of each periodic examination and repair, and the name and signature of the competent person who carried out the periodic examination or repair; | Pass |
| 2) next due date of periodic examination. | Pass |

Note. It is the responsibility of the user organisation to provide the record and enter into the record the details required.

4.7 Periodic examination

Manufacturers shall provide all the necessary information and equipment e.g. instructions, checklists, spare parts lists and special tools etc, to enable periodic examinations to be carried out by a competent person. Pass

Estimates of the uncertainty of measurement

Clause	Test	Uncertainty
4.1	Design & ergonomics	-
4.1.6	Materials and construction – Length of lanyard	±3.1 mm
4.2	Materials	-
4.3	Terminations	-
4.3.4	Terminations – Length of knot tail	±1.8 mm
4.4	Slippage	±1.0%
4.5	Static strength	*
4.6	Dynamic strength	*
	Static strength after dynamic strength	*
4.7	Corrosion	*
4.8	Marking and information	-
6	Marking	-
7	Information	-
8	Packaging	-

* The acceptance criterion for this test is a straightforward "Pass/Fail", rather than a numerical value. Consequently, as there is no value to be reported, uncertainty has not been reported either.

Values expressed as a percentage (%) are relative.

It should be noted that the above values have not been taken into account when making assessment to the pass/fail criteria.

ANNEX

This Annex comprises one section.

1. Photograph of the product tested. (1 page)

END OF REPORT

**Jinhua Jech Tools Co., Ltd. –
Lanyard, model JE900018**



INSPEC Testing Services' specimen 2G07901

5 June 2019